



1019 SE Holbrook Ct.
 Port St. Lucie, FL 34952
 772-335-8225 - 800-775-9474 - Fax772-335-3991
 SIC CODES: 3089 & 5169 DUNS: 00-306-7852



Distributors Worldwide Email: sales@enviroseal.com Web: <http://www.enviroseal.com>

Typical Application Rates For Enviroseal Products

Topical Application rates for M10+50™	Ft2/Gal	Gal/Acre	M2/Liter	Liter/M2	Parts Water
Dust Control 90 days	600	70	16	0.05	7-15
Dust Control 6 Months	400	110	10	0.1	5-10
Dust Control 12 Months	300	140	7	0.15	2-10
Slope Erosion Control	150	250	4.5	0.2	2-5
Stockpile Dust Cap	250	170	6	0.2	5-8
Unpaved Runway-Light Duty	35	1250	1	1	2-4
Helicopter Pad	35	1250	1	1	2-4
Pond Lining	20	2200	0.5	2	1.5

These rates are generalized and are dependant on soil type, soil moisture, weather conditions, and intended final use. We suggest testing be performed on soil first to determine suitability and more accurate application amounts.

Full Depth Mix Enviroseal M-10+50™	Gallon- Cubic Yard	Liters- Cubic Meter
ADA Trails, Cart Paths	6-10	23-38
Unpaved Runway-Military Specification	16	61
Roadway-Light Duty	6-10	23-38
Roadway-Heavy Duty/Haul Road	10-12	38-46

The amount of water to use is the difference between in-situ moisture and optimum soil moisture required for compaction of the soil being treated. We suggest laboratory testing be performed prior to application to determine increases in specific engineering qualities of the soil being treated.